





# 6-Way Ball Valve



6 Way Ball Valve is designed for Duplex Filters to achieve smooth changeover between the filters. The Valves can be supplied in sizes from 1½ inch to 8 inch full bore. The of Construction Material offered in this range of products is: ASTM A216 Gr WCB Body with CF8/ SS304 trims, ASTM A351 Gr CF8 Body with CF8/ SS304 trims, ASTM A351 Gr CF8M Body with CF8M/ SS316 trims Super Duplex SS Body with Super Duplex SS trims

## **Applicable standards**

- Design standard: ISO17292/ ASME B16.34
- Testing standard: BS6755/ API598
- Pressure-Temperature rating: ASME B-16.34
- Flange Dimensions: ASME B-16.5

### **Product Specification**

- Size: 1½" to 10" For Flanged End
- Class: 150#, 300#
- Material: SS316, SS304, Duplex SS, Inconel, Hastelloy
- Port: Full Port
- End connection: Flanged End,
- Operation: Manual till 3", above 3" Geared Actuator is provided

### **Features that Add value**

- Designed for duplex filter and duplex heat exchanger.
- Easy to operate.
- Smooth changeover between filters.
- Low maintenance cost
- Available with rigid coupling
- Available in L-port and T-port configurations
- Zero leakage
- Easy Installation and Operation



ØHXN

16 X 4

19 X 4

19 X 4

19 X 8

22.22 X 8

ØF

98.6

120.6

152.4

190.5

241.3

ØR

73

127

157.2

216

14.3

16

19

24

25.4

30.6

ØB

38

50

75

100 190

150

250

92

107

140

225

348

400

165

175

220

265

424

700


125


150


190

280

## **Technical Specifications**







#### ALL DIMENSIONS IN MM

### **CONTACT DETAILS**

Head Office: 423, Nazar Camp Cross 3, Main Road, Vadgaon, Belagavi - 590005, Karnataka, India Factory Address: 103/3, Dewarwadi Village, Chandgad Taluk, Kolhapur Dist, Maharashtra - 416507, INDIA

**Phone:** ++91-831-2482327/ 2484635 | **Mob. :** ++91-9243210643/ 9243222573

E-mail: sales@kavaatavalves.com