

- » Support to seal Stainless steel plate.
- » Spring Stainless Steel.
- » End threads BSP to ISO 228 at both ends.
- » Temp. Working: -20 to 100 degree C.
- » Flow indicator, size & pressure range permanently marked on the surface.


Advantages

- » No direct metal to metal sealing.
- » Silent.
- » Quick closing.
- » Capable of handling extra weight of piping installations. » Prevents loss of water pressure in the building.

Benefits


- » Prevents water backflow. (Zero leakages.)
- » Prevents water hammer.
- » Prevents loss of prime in the pump systems.

Size Specification



PART NO.	SIZE	DN	A	В	PN	
NRV 050	1/2"	15	58.5	34.5	25	
NRV 070	3/4"	20	65	41.5	25	
NRV 100	1"	25	74.5	48	25	
NRV 125	1 1/4"	32	83	60.5	18	
NRV 150	1 1/2"	40	93	71	18	
NRV 200	2"	50	101	87	18	
(All dimensions are in mm)						

Material Specification



POS.	DESCRIPTION	MATERIAL
1	Body	CW617N
2	Pin	CW614N
3	Spring	SS 302
4	Plate	SS 304
5	Washer	NBR
6	Plug	CW614N
7	Adhesive	THREAD SEAL
8	Nut	CW617N